



EG-530YD-XX	EG-530KD-XX	EG-530AD-XX
		

型号 Model	额定电 压 Voltage (V)	工作电 压范围 Voltage Scope (V)	额定转 矩 Torque (mN.m)	工作转 矩范围 Torque Range (mN.m)	额定转速 Speed (r/min)	额定电流 Current (mA)	起动转矩 Starting Torque (mN.m)	漂移 Drift (%)	寿命 Life (H)	旋转方向 Direction of Rotation (CW, CCW)
EG-530YD-9F/B	9	6.3~ 11.3	0.98	0.49~ 1.47	2000/4000	≤145/≤150	4.90at6.3V	≤1.0%	1000	CW (CCW)
EG-530YD-2F/B	12	8.4~15	0.98	0.49~ 1.47	2000/4000	≤110/≤115	5.39at8.4V	≤1.0 %	1000	CW (CCW)

型号 Model	额定电 压 Voltage (V)	工作电 压范围 Voltage Scope (V)	额定转 矩 Torque (mN.m)	工作转 矩范围 Torque Range (mN.m)	额定转速 Speed (r/min)	额定电流 Current (mA)	起动转矩 Starting Torque (mN.m)	漂移 Drift (%)	寿命 Life (H)	旋转方向 Direction of Rotation (CW, CCW)
EG-530KD-9F/B	9	6.3~ 11.3	0.88	0.69~ 1.08	1600/3200	≤115/≤130	4.41at 6.3V	≤1.0%	1000	CW (CCW)
EG-530KD-2F/B	12	8.4~15	0.88	0.69~ 1.08	1600/3200	≤95/≤110	1.91at8.4V	≤1.0 %	1000	CW (CCW)

型号 Model	额定电 压 Voltage (V)	工作电压 范围 Voltage Scope (V)	额定转 矩 Torque (mN.m)	工作转 矩范围 Torque Range (mN.m)	额定转 速 Speed (r/min)	额定电 流 Current (mA)	起动转矩 Starting Torque (mN.m)	漂移 Drift (%)	寿命 Life (H)	旋转方向 Direction of Rotation (CW, CCW)
EG-530AD-6F/B	6	4.2~7.5	0.88	0.69~ 1.08	2400±2 %	≤145	3.92at4.2V	≤1.0 %	1000	CW (CCW)
EG-530AD-9F/B	9	6.3~ 11.3	0.88	0.69~ 1.08	2400±2 %	≤115	4.41at6.3V	≤1.0 %	1000	CW (CCW)
EG-530AD-2F/B	12	8.4~15	0.88	0.69~ 1.08	2400±2 %	≤85	4.91at8.4V	≤1.0 %	1000	CW (CCW)