



### SPECIFICATIONS

**Electrical**  
 Current Rating: 5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Operating Temp.: -25°C ~ +85°C  
 Insulation Resistance: 1000MΩ/ min.  
 Dielectric Withstanding Voltage: 1500V AC/ min.  
 Contact Resistance: 10mΩ/ max.

**Material**  
 Material: Nylon66, UL94V-2  
 Terminal Material: Brass/ Tin-plated

Poles	Dimension mm (in.)	
	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.60
11	39.60	43.56
12	43.56	47.52
13	47.52	51.48
14	51.48	55.44
15	55.44	59.40
16	59.40	63.36
17	63.36	67.32
18	67.32	71.28
20	75.24	79.20

<b>RoHS Compliant</b>			
APPD. 核准 Betty		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖 Betty		SCALE 比例 參考	
DATE 列表日 2012/04/20	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號
	PAGE 張數 1 OF 1	REV. 版本 B	